


- Single acting, double speed operation
- 4 different models from 1.000 up to 2500 bar
- Automatic switching from high and low pressure
- Suitable design for bolt-tensioning and testing
- Internal pressure relief for maximum security
- OD Ø100 mm precision gauge available in all models
- Pump head high strength steel, tank made of aluminum
- Compact, lightweight, ergonomic design for easy transport



*This hand pump can be used with all BOLTIGHT 1000 bar tooling and equipment. The pump has both high and low pressure pistons and is supplied complete with, a 110 mm damped (liquid filled) pressure gauge, pressure release valve, internal pressure safety relief valve, a 2.4 liter oil reservoir and a self sealing quick connect coupling (Type A – see DS26).*

*Hand pumps should only be used with one or two tensioning tools. When simultaneous operation of several tools is being considered BOLTIGHT recommends the use of an air driven pump.*

Model		BT-1015	BT-1515	BT-2015	BT-2515
Working Pressure	bar	1.000	1.500	2.000	2.500
Pump type	**	Double Speed	Double Speed	Double Speed	Double Speed
Reservoir capacity	cm <sup>3</sup>	2.400	2.400	2.400	2.400
Oil Displacement (LP/HP)	cm <sup>3</sup>	20 / 1	20 / 0,7	21 / 0,7	22 / 0,8
Pressure Gauge	bar	0...1500	0...1500	0...3000	0...3000
Handle Effort at max. Pressure	kg	23	37	42	42
Oil port	NPT	¼"	¼"	¼"	¼"
Weight	kg	10	10	11	11
Sizes (L x W x H)	cm	620x130x170	620x130x170	620x130x170	620x130x170