

- Clutch to connector bolt holes and spread flange joints
- Designed for zero gap flange joints
- Does not damage to flange surface
- Works with 700 bar hydraulic hand pump
- Dual usage recommended for large flanges
- Provide maximum security for flange spread operation
- Suitable for 38 mm and 108 mm diameter connection holes
- Holder grips are available for every bolt diameter
- Accelerates the flange separation process, reduces costs
- Service and replacement parts support in Turkey



Hydraulic Series

Inline Hydraulic Series

SG-13TE

38.0mm - 49.0mm
1.49" - 1.92"

SG-15TE

47.5mm - 62.0mm
1.87" - 2.44"

SG-18TE

59.5mm - 75.0mm
2.34" - 2.95"

SG-25TE

75.0mm - 108mm
2.95" - 4.25"

Product Details	Unit	SG-13TE	SG-15TE	SG-18TE	SG-25TE
Spread Force	Ton	13	15	18	25
Bolt Hole	Mm	38 - 49	47.5 - 62	59.5 - 75	75 - 108
Grip Holder	Mm	M39 - M42 - M45	M48 - M52 - M56	M60 - M64 - M70	M76 - M80 - M84 - M90 - M95 - M100
Tool Weight	Kg	21.5	26	14	24
With Case Weight	Kg	40.5	45	45	50

Equalizer zero gap grip-holder mechanical flange spreader is clutch to connector bolt holes and spread flange joints. On this case there is no space on flange surface. This is why MG and SW series not using on zero gap flange types. (MG series requires 2 mm gap, SW series requires 6 mm gap.)

