

# Stephan Dahlmann

Mechanic und Antriebstechnik GmbH

## HDF 2500 Bar Electric Driven Hydraulic Test Pump

- Gauge Ø 100mm, Class 1.0 glycerine filled, 2500bar / 35.000 Psi
- Cejn 135 Series quic release female coupling
- Manually adjustable 0...2500 bar infinitely variable pressure valve
- Security remote control 24V DC with 5m cable
- Industrial inline oil filter
- Steel protecting frame with rubber feet
- Oil sight glass
- Made in Germany



Model Code	HDF2500-750-230V	HDF2500-750-115V
Voltage	230 Volt	115 Volt
Nominal Power Out	0,75 kW	
Flow Rate	3,5 liter/ min	
Low Pressure up to 30 bar	3,5 liter/ min	
High Pressure at 2500 bar	0,27 liter / min	
Weight with oil	37,5 Kg	
Oil Tank Capacity	5 Liter	
Dimensions (L+W+H)	450 x 32 x 430 mm	
Noise Level	82 db (A)	

### Surkon Makina Sanayi ve Ticaret LTD. ŞTİ.

İvedik Organize Sanayi Bölgesi - Özpetek Sanayi Sitesi 1390 Sokak No: 12 - TR-06378 - Yenimahalle / ANKARA  
Tel: +90 (312) 386 14 64 / Faks: +90 (312) 386 14 88 / info@surkon.com / www.surkon.com



ISO 9001: 2008  
Quality Management System  
TS EN ISO / IEC 17021  
AB-0049-YS  
Certificate No: 57812

**SURKON**  
INTERNATIONAL