

KIT CONSISTS OF:

- D0111, Door opener tool
- Hand pump, with swivel coupling
- 2 m hose with quick couplings
- Crowbar
- Urethane hammer
- Couplings for convinence
- Carrying case

FEATURES OF THE DO111

- Quick and easy to use
- 105 mm stroke
- 13 ton capacity
- Spring return
- Equipped with a male quick coupling as standard
- Works in any position, horizontal or vertical
- Swivel coupling for greater flexiblity



Hydraulic door opener kit

EHR111A - D0111

The door opener DO111 is the perfect tool for rescue and police where forced entry operations are necessary.

Information



Place the DO111 in position, appply pressure by pumping the hydraulic pump until the door breaks open. The tool can work in any position, horizontal or vertical which makes the D0111 quick and easy to use.

Functionality



The DO111 is provided with a flat surface, which enables the tool to be hammered in to the door slot. Furthermore, it

has serrated teeth for holding a steady grip between the door and frame.



Usability




Fields of use where the DO111 is applicable may include:

- Rescue services
- Civil defence
- Emergency aid operations




D0111 - PERFORMANCE

| | Capacity kN ton | | Max workin | g pressure | Stroke | | Stroke volume | | | |
|---|------------------------|----|------------|------------|--------|------|-----------------|-----------------|--|--|
| | | | MPa | psi | mm | inch | cm ³ | in ³ | | |
| Ì | 127 | 13 | 80 | 11603 | 105 | 4.13 | 167 | 10.19 | | |



DO111 - MEASUREMENTS & DATA

| A | | В | | C | | D | | E | | F | | G | | Н | | I | | Weigh | t |
|-----|-------|-----|-------|------|-------|----|-------|-----|-------|----|-------|----|-------|----|-------|-----|------|-------|------|
| mm | inch | mm | inch | mm | inch | mm | inch | mm | inch | mm | inch | mm | inch | mm | inch | mm | inch | kg | lbs. |
| 208 | 8.189 | 120 | 4.724 | 57,1 | 2.248 | 25 | 0.984 | 105 | 4.134 | 1 | 0.039 | 19 | 0.748 | 89 | 3.504 | 100 | 3.94 | 4.9 | 10.8 |



The swivel coupling is capable of rotating 360° even under pressure which guarantees highest possible flexibility when handling the tool.

PUMP

Hand pump - PHS80-300W



Working pressure: 80 MPa, 800 bar, 11600 psi

Effective oil volume: 300 cm³, 18.3 in³

Capacity high pressure: 1 cm³/stroke, 0.1 in³/stroke Capacity low pressure: 20 cm³/stroke, 1.2 in³/stroke

Pump force: 400 N Weight: 4,8 kg, 10.6 lbs

In EHR111A, equipped with swivel ASE10 and female quick coupling AQI8-LD

ORDERING INFORMATION

| Designation | EHR111A - complete to | ol kit | | | | |
|-------------|--------------------------|------------------------|-----------------------|-------------------------------|----------------------------|--|
| Part number | 51152 | | | | | |
| Designation | DO111 - Door opener tool | PHS80-300W - Hand pump | Swivel coupling ASE10 | Quick coupling female AQI8-LD | Quick coupling male AQU8-D | |
| Part number | 44124 | 44881 | 37588 | 45950 | 45953 | |

REHOBOT Hydraulics AB

Postal address: P.O. Box 1107
631 80 Eskilstuna, Sweden
T: +46 (0)16-16 82 00 | F: +46 (0)16-13 93 16
E: info@rehobot.se | www.rehobot.se

REHOBOT Ltd.

Unit 6, Stechford Trading Estate, Lyndon Road, Stechford Birmingham B33 8BU, UK
T: +44 121 789 77 07 |F: +44 121 789 68 66
E: info@rehobot.co.uk | www.rehobot.co.uk

REHOBOT Inc. Unit #1 3980 W. Albany St. McHenry II 600 50, USA T: +1 815 385 77 77 |F: +1 815 385 77 76 E: info@rehobot.us|www.rehobot.us