



Elektrod Tork Anahtarları

Elektrode Torque Wrenches



- » Tekrarlanabilir tork uygulama hassasiyeti $\pm 4\%$.
- » 3.200 N.m'ye kadar 10 farklı tork anahtarı.
- » 600 mm çapa kadar elektrodlar için kullanılabilir.
- » Dişli çeneleri sayesinde elektrodu kavrar, kaymaz.
- » Tork erişimini rahatlıkla hissedilir ve işlem tamamlanır.
- » N.m ve lbf.ft iki göstergeli tork ayar paneli.
- » Her cihaz Norbar kalibrasyon sertifikasıyla sevk edilir.
- » Ekstra ağır çalışma şartlarına uygun tasarım.

- » Repeatable torque application accuracy $\pm 4\%$.
- » 10 different torque wrenches up to 3.200 N.m.
- » Can be used for electrodes up to 600 mm diameter.
- » Self-clamping action speeds the tightening operation
- » Unmistakable signal when the set torque is reached.
- » Long scale length in N.m and lbf.ft allows error free setting.
- » Every wrench is supplied with a calibration certificate.
- » Designed for extra heavy working conditions.

Hafif İş Serisi / Low Range

Parça Part	Tork Aralığı Torque Range		Elektrod Çapı Electrode Diameter		Uzunluk Length	Ağırlık Weight	
	No.	N.m	lbf.ft	Ø inch			Ø mm
	12506	44 - 312	33 - 230	8"	200	928	3.2
	12530	146 - 542	110 - 400	10"	250	1.140	6.8
	12531	205 - 780	150 - 575	12"	300	1.280	8.4



Ağır İş Serisi / High Range

Parça Part	Tork Aralığı Torque Range		Elektrod Çapı Electrode Diameter		Uzunluk Length	Ağırlık Weight	
	No.	N.m	lbf.ft	Ø inch			Ø mm
	12532	350 - 1.140	260 - 840	14"	350	1.767	13.8
	12533	350 - 1.300	260 - 950	16"	400	1.810	14.3
	12535	750 - 1.500	550 - 1.110	18"	450	1.720	16.5
	12536	1.000 - 2.000	750 - 1.475	20"	500	2.200	20
	12537	1.200 - 2.370	900 - 1.750	22"	550	2.555	25.4
	12538	1.200 - 2.370	900 - 1.750	24"	600	2.590	26.1
	12538.HD	1.600 - 3.200	1.200 - 2.360	24"	600	3.335	31.7

