



Modell	Arbets-tryck MPa	Kapacitet cm <sup>3</sup> /slag	Effektiv oljevolym cm <sup>3</sup>	Pump-kraft N	P tryck-anslutning	A mm	B mm	C mm	D mm	E mm	F mm	G mm	H mm	K mm	L Ø mm	Vikt kg
PH70A-600	70	2.9	600	450	G1/4"	590	170	90	68	56	540	68	84	7	6.6	4.5
PH70A-1000	70	2.9	1000	450	G1/4"	590	170	110	80	75.3	575	68	84	7	6.6	5.2
PH80A-600	80	2.9	600	515	G1/4"	590	170	90	68	56	540	68	84	7	6.6	4.5
PH80A-1000	80	2.9	1000	515	G1/4"	590	170	110	80	75.3	575	68	84	7	6.6	5.2

DENNA RITNING ÄR REHOBOT AB:s EGENDOM. SKYDDAD ENLIGT GÄLLANDE LAG.  
 THIS DRAWING IS THE PROPERTY OF REHOBOT AB. PROTECTED BY PREVAILING LAW.

Material	Blank, dimension	Heat treatment	Surface treatment
-	-	-	-
Permissible deviations for dimensions without indication of tolerances			Surface roughness unless specified
Machined parts	Castings	Fuse welded constr.	✓ Ra µm
acc.SS-ISO-2768-1	acc.SS-ISO-8062	acc.SS-EN ISO 13920	
Designed by	Drawn by	Date	Product
CS	-	28-Jul-09	PH-PUMPAR
Prod.appr.	Design appr.	Scale	Title
WH	VTA	1:2	
2010-05-17	2010-05-17		<b>REHOBOT®</b>
			Måttitning
			Replaces
			Replaced by
			C-49099

Issue	Change	Position	Date	Sign.
8		7		6